





















Technical specifications

Westbond W1500 carpet tiles meet the requirements of EN 1307

W1500 – Colour Dyed

| | | |
|---|---|---|
| | Description | Fusion bonded carpet tiles |
|  | Dimensions | 50cm x 50cm (special sizes available on request up to 1m x 1m) |
|  | Total thickness | 10.0mm ± 10% |
|  | Pile height | 7.5mm ± 10% |
| | Made to order collection | 144 colours and infinite custom flex combinations available to order from 1m ² . 3.5m ² per box. |
|  | Application | EN 1307 Class 33 |
|  | Comfort class | LC5 |
| | Pile composition | 80% Undyed British wool / 10% polyamide / 10% polyester |
| | Dye method | Hank dyed |
| | Pile density | 0.166 grams per cm ³ |
| | Number of points | 356,000 per m ² ± 10% |
|  | Pile weight | 1,500 gsm ± 10% |
| | Effective pile weight | 1,300 per m ² ± 10% |
| | Total weight | 4,500 gsm ± 10% |
|  | Tile backing | PVC incorporating at least 70% pre-consumer recycled content |
|  | Castor chair use | EN 985 Minimum R Value: ≥ 2.4 |
|  | Light fastness | EN ISO 105-B02 ≥ 4 |
|  | Dimensional stability | EN 986 < 0.2 % |
| | Squaring | Max ± 0.1% |
| | Curling | < 2mm |
| | Fraying | 0 |
|  | Impact sound reduction | ISO 140-8 32 dB |
| | Sound absorption | ISO 354 0.20 (Classification E) |
|  | Creating Better Environments | |
|  | Renewable Electricity | Westbond carpet tiles are manufactured using 100% electricity made from renewable sources. |
|  | Recycled Content | All Westbond carpet tiles utilise a mixed vinyl waste backing which contains at least 70% pre-consumer recycled content. |
|  | Indoor air quality | Pass AGBB |
| | Ska Rating | Westbond carpet tiles meet Ska Rating criteria for M12 soft floor coverings |
|  | Guarantee | Westbond is guaranteed for 7 years under heavy contract use.* *Provided that the carpet tiles have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Westbond requirements currently in force. |
|  | Installation method | Monolithic |
| | Westbond fusion bonded carpet tiles meet the requirements of EN 14041 | |
|  | Reaction to fire | EN 13501-1 B _{fl} -s1 |
|  | Slip resistance | EN 13893 ≥ 0.30 |
|  | Electrical resistance | IBM/ICL |

Our recommended adhesive for our collection of Westbond carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

The Westbond sales organisation and manufacturing site has certified quality, environmental and safety management systems in accordance with ISO 9001/18001/14001. All Westbond products are manufactured in a SA8000 certified facility.

Westbond reserves the right to change the specification of its products without giving prior notice.

For more information please contact:

Westbond,
Cortonwood Drive,
Cortonwood Business Park,
Brampton, Barnsley,
South Yorkshire UK
Tel: +44 (0)1226 757 757

www.westbondcarpets.co.uk